



# Laundry Presses – Air operated

## FPA1-WC, FPA2-WC, FPA3-WC




### Features and benefits

- High temperature stainless steel polished head dries the fabric and gives it a flat finish
- High pressure achieves an excellent finish
- Adjustable pressure regulator for pressing different fabrics achieves an excellent finish
- Air operated reduces operator fatigue and allows high production output
- Two button closing improves operator safety
- High quality padding and cover for buck reduces impressions
- Easy installation and operation due to no vacuum needed and therefore no pedal


### Main options

- Integral steam boiler – 9 kW
- Integral air compressor
- Electric steam iron
- Safety head guard (CE) improves operator safety
- Adjustable release timer simplifies the operation and ensures consistent results
- Water spray gun with support and condenser


| Electrical connections                  | Standard                                |   | Optional        |                    |                     |
|---|---|---|-----------------|--------------------|---------------------|
|   |   |   | Built-in boiler | Built-in air comp. | Electric steam iron |
| Voltage, standard                       |   |   |                 |                    |                     |
| 208-240V 1 AC 50/60 Hz                  | kW (A)                                  | -                                       | -               | -                  | 0.8 (6)             |
| Voltage, built-in boiler                |   |   |                 |                    |                     |
| 230V 3 AC 50/60 Hz                      | kW (A)                                  | -                                       | 9 (25)          | 0.75               | -                   |
| <b>Steam, air and vacuum connection</b> |   |   |                 |                    |                     |
| Steam                                   | DN                                      | 15                                      | -               | 15                 | 15                  |
| Rec. steam pressure                     | kPa                                     | 700                                     | -               | 700                | 700                 |
| Steam consumption                       | kg/h                                    | 20                                      | -               | 20                 | 20                  |
| Condensate                              | DN                                      | 15                                      | -               | 15                 | 15                  |
| Compressed air                          | DN                                      | 10                                      | 10              | -                  | 10                  |
| Rec. air pressure                       | kPa                                     | 700                                     | 700             | -                  | 700                 |
| Air consumption                         | l/min                                   | 6 l/cycle                               |                 |                    |                     |
| <b>Shipping data</b>                    |   |   |                 |                    |                     |
|   | net, kg                                 | 326                                     | + 46            | + 46               | + 6                 |
|   | crated, kg                              | 356                                     | + 46            | + 46               | + 6                 |
| <b>Dimensions in mm</b>                 |   |   |                 |                    |                     |
| <b>A</b> Width                          |   | 1250                                    | 1250            | 1250               | 1250                |
| <b>B</b> Depth                          |   | 920                                     | 920             | 920                | 920                 |
| <b>C</b> Height                         |   | 1250                                    | 1250            | 1250               | 1250                |
| <b>D</b>                                |   | 1450                                    | 1450            | 1450               | 1450                |
| <b>E</b>                                |   | 800                                     | 800             | 800                | 800                 |
| <b>F</b>                                |   | 1030                                    | 1030            | 1030               | 1030                |
| <b>G</b>                                |   | 1190                                    | 1190            | 1190               | 1190                |
| <b>H</b>                                |   | 360                                     | 360             | 360                | 360                 |
| <b>I</b>                                |   | 220                                     | 220             | 220                | 220                 |
| <b>J</b>                                |   | 470                                     | 470             | 470                | 470                 |
| <b>K</b>                                |   | 205                                     | 205             | 205                | 205                 |
| <b>L</b>                                |   | 520                                     | 520             | 520                | 520                 |
| <b>M</b>                                |   | 260                                     | 260             | 260                | 260                 |
| <b>N</b>                                |   | 1490                                    | 1490            | 1490               | 1490                |
| <b>1</b> Control panel                  | <b>4</b> Condensate                     | <b>7</b> Boiler drain (built-in boiler) |                 |                    |                     |
| <b>2</b> Electrical connection          | <b>5</b> Compressed air                 |   |                 |                    |                     |
| <b>3</b> Steam connection               | <b>6</b> Water supply (built-in boiler) |   |                 |                    |                     |



Utility shape  
FPA1-WC shown



Utility/legger shape  
FPA2-WC shown



Mushroom shape  
FPA3-WC shown

