



# Professional Washer

## PW9C

### Features and benefits

- **Compass Pro® microprocessor offers:**
  - Large display and one control knob for easy program selection
  - Language selection
- PW9 is a large capacity washer suitable for professional users
- Four compartment detergent box for manual dosing of powder or liquid detergent
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- Large door opening for easy loading/unloading
- Drain pump
- Electrical connection: 3 phase or 1 phase
- Water hoses included

### Options

- Coin meter
- Drain valve



Images shown are a representation of the product only and variations may occur.

Main specifications		PW9C	
Capacity, max.	kg/lb	9/20	
Extraction	rpm	1015	
G-factor		300	
Heating alternatives	electricity 3 AC	5.4 kW	
	electricity 1 AC	3.6 kW	
	non-heated	x	
<b>Consumption data "Colour 60°C" without Pre-wash*</b>		5.4 kW	3.6 kW
Total time	min	50	54
Water consumption (cold/hot)	litre	89/17	89/17
Energy consumption (motor/heating)	kWh	0.25/0.65	0.25/0.65

\* Water temperature 15°C cold water and 65°C hot water



Electrical connections*					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended fuse A
		Hz			
Electric heated	220-240V 1 ~	50/60	3.0/5.4	3.1/5.5	16/25
	380-415V 3N ~	50/60	3.0/5.4	3.1/5.5	16/25
Steam or Non heated	220-480V 1/3 ~	50/60	-	1.0	10

Water and steam connection		PW9C	
Water valves	DN	20	
Water pressure	kPa	150-400	
Capacity at 300 kPa	l/min	16	
Drain valve (optional)	ø mm	50/75	
Draining capacity	(pump) l/min	30	
	(drain valve) l/min	160	
Liquid detergent supplies (optional)		3	
Floor requirements			
Frequency of the dynamic force	Hz	16.9	
Floor load at max extraction	kN	1.4 ± 0.5	
Sound levels			
Airborne sound level	dB(A)	71	
Heat emission			
% of installed power, max		5	
Shipping data*			
Weight	net, kg	135	
Shipping volume	m <sup>3</sup>	0.81	
Dimensions in mm			
A	Width	720	
B	Depth	1130	
C	Height	1113	
D		408	
E		721	
F		831	
G		80	
H		1030	
I		224	
J		124	
K		1010	
L		910	
M		278	
N		98	
O		239	
1	Operating panel	6	Liquid detergent supply
2	Door opening ø 310 mm	7	Drain valve
3	Detergent box	8	Electrical connection
4	Cold water	9	Steam connection
5	Hot water	10	Re-used water

\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

