

TUMBLE DRYERS

LDR1025, LDR1425, LDR1700

FEATURES

- Full OPL microprocessor
- Gas, Steam heating ,
Electrical heating (LDR1025)
- Large door opening
for easy loading
and unloading (Ø68cm)
- Galvanized drum
- Radial airflow
- Standard reversing drum
- Self-cleaning lint screen
- Preheating of intake air


OPTIONS

- Stainless steel drum
- Stainless steel front panel
- Residual moisture control Sensodry+®:
 - lower energy and utility costs
 - lower linen replacement costs
- SafeTech™ Fire Suppression System



TYPE		LDR1025 EL	LDR1025 GAS	LDR1025 STEAM (HIGH PRESSURE)	LDR1425 GAS	LDR1425 STEAM (HIGH PRESSURE)	LDR1700 GAS	LDR1700 STEAM (HIGH PRESSURE)
CAPACITY	kg	55			77		90	
DIMENSIONS DRUM								
Drum volume	l	1021			1408		1656	
Drum diameter	mm	Ø1118			Ø1289		Ø1289	
AIR FLOW	l/s	755			1156		1156	
HEATING	kW	60	79	119	116	190	125	190
MOTOR								
Drum	kW	0.560			0.560		0.560	
Fan	kW	0.746			2.238		2.238	
CONNECTION								
Electrical	AC/Hz	3×200-240V 50/60Hz, 3×380-415V 50 Hz, 3×380-415/440V 60Hz						
		Others on request			Others on request		Others on request	
Gas inlet	inch	-	1	-	1	-	1	-
Steam inlet	inch	-	-	3/4	-	3/4	-	3/4
Air outlet	mm	254			305		305	
	inch	10			12		12	
DIMENSIONS								
H×W×D unpacked	mm	2177×1178×1725			2388×1349×1749		2388×1349×1939	
H×W×D packed	mm	2286×1232×1829			2519×1473×1892		2515×1413×2019	
WEIGHT								
Net	kg	578	578	624	714	760	790	820
Gross	kg	607	607	656	756	806	855	855

The data concerning dimensions of machines include all extended parts



Lavamac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.