

Drying cabinet

DC6-4 with heat pump

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Braille script
- Insulated doors for quiet operation and robust design
- 30 extensible hangers for easy loading/unloading
- Flexible installation with adjustable feet
- Reversible door - left or right hanging



Long-term savings

By using a Drying Cabinet with a Heat Pump, not only can you avoid exhaust connection but you can reach energy saving of 50% compared with an electric version. There are two options of heat pump versions both are equipped with a built in condensing pump



Productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

Safety

Option to activate child safety start lock and the magnetic edge of doors eliminates risk of children being locked in.

Accessories

Glove hanger for more efficient drying of gloves, hats etc.
 Glove hanger: 988704085, 432730569



Main specifications		DC6-4
Rated capacity	kg	4
Evaporation*	g/min	30
Drying time cotton*	min	67
Rated input	kW	1.2
Energy/load of linen	kWh/kg	0.29
Energy/water evaporated	kWh/l	0.58

* Applies to 4 kg dry weight cotton with 50% residual moisture.

Electrical connection		DC6-4
Voltage	230V 1AC 50-60 Hz kW(A)	1.2(10)
Sound level		
Sound power/pressure level at drying*	dB(A)	<62
Heat emission		
Average heat emission per drying cycle used to assess ventilation need**	kW	0.6
Weight		
	net kg	95
Dimensions in mm		
A	Width	595
B	Depth	665
C	Height	1910
D		1925
E		15
F		1075
G		290
H		850
1 Operating panel 2 Condensation nipple \varnothing 10 mm and 1.5 m hose included 3 2.5 m connecting cable included		

Colour of front and side panels is silver grey and handle is dark blue.

* Sound power levels measured according to ISO 60704.

** For assistance with dimensioning necessary ventilation needs, contact authorized ventilation technician.

For sufficient ventilation all sources introducing heat need to be taken into account plus all other parameters effecting the ventilation need. Climate zone, building parameters, room size, etc.

