

Rotary Finishing Cabinets

FRC1, FRC2, FRC3



Features and benefits

- Even distribution of steam moistens the fabric to remove creases
- Hot air blowing presses and dries the fabric
- Body form with extending shoulder, shapes and supports the garment
- Range of sleeves/clamps improve the finish
- Trousers waist expander shapes and supports the garment
- Microprocessor, stores various programmes
- Adjustable air blowing baffle, suitable for various fabric types
- Integral 10 or 12 kW steam boiler, simplifies the installation

Main options

- Automatic start on door closing, simplifies the operation
- Suspended all steam iron, enables hand finishing
- Additional body form/trouser support for high volume production
- Multiple hanger device, enables conditioning garments on hangers
- External blower, for pre-forming/post finishing
- Additional heating – 15 or 18 kW boiler

Electrical connections		FRC1	FRC2	FRC3
Voltage				
208-240V 3 AC 50/60 Hz	kW	0.75	0.75	0.75
400-415V 3N AC 50 Hz	kW	0.75	0.75	0.75
Voltage, built-in boiler				
208-240V 3 AC 50/60 Hz	10 kW	11.4	11.4	11.4
380-400V 3N AC 50 Hz	12 kW	13.4	13.4	13.4
	15 kW	16.4	16.4	16.4
	18 kW	19.4	19.4	19.4
Steam and water connections				
Steam	DN	15	15	15
Rec. steam pressure	kPa	500	500	500
Steam consumption	kg/h	16-20	16-20	16-20
Condensate	DN	15	15	15
Water supply	ø mm	12	12	12
Boiler drain	DN	15	15	15
Shipping data				
	net, kg	205	270	205
	crated, kg	235	300	235
	boxed, kg	295	360	295
Dimensions in mm				
A	Width	1100	1100	1100
B	Depth	1050	1050	1050
C	Height	2040	2040	2040
D		1840	1840	1840
E		870	870	870
F		1530	1530	1530
<ol style="list-style-type: none"> 1 Control panel 2 Electrical connection 3 Steam connection 4 Condensate 5 Boiler drain (built-in boiler only) 6 Water supply (built-in boiler only) 7 Air exhaust 				

Please note:

The following configuration is available:

FRC1: Trouser device + Body Form

FRC2: Body Form + Body Form

FRC3: Trouser device + Trouser device

